


## Hose For Foods & Water Delivery



**TOYOX**

**Features -** (Food Safety Law)  
Main material - Soft PVC + Plasticizer (Non Phthalic Acid).  
Reinforcement - Polyester threads.

**Specifications -** Working temperature range (-)5-70°C.

**Advantages -** Resistance to fats and oils - Conform to food safety law. Pliability/Heat resistance(70C) - Easy to handle. Safe for food applications. Transparency - Safe because the fluid flow can be verified.

### A - Universal Food Grade Delivery Hose

Price/Roll		Price/Meter		I.D. X O.D. (mm)	Working Pressure Mpa(kgf/cm <sup>2</sup> )	Gross Weight (Kg/Roll)	Length (m)
Number	Price ฿	Number	Price ฿				
235H 1257	—	335H 1257	—	6 X 11	0~10	9	100
235H 1258	—	335H 1258	—	8 X 13.5	0~10	13	100
235H 1259	—	335H 1259	—	9 X 15	0~10	15	100
235H 1260	—	335H 1260	—	10 X 16	0~10	16	100
235H 1261	—	335H 1261	—	12 X 18	0~8	19	100
235H 1262	—	335H 1262	—	15 X 22	0~8	27	100
235H 1263	—	335H 1263	—	19 X 26	0~6	16	50
235H 1264	—	335H 1264	—	25 X 33	0~6	25	50
235H 1265	—	335H 1265	—	32 X 41	0~4	35	50
235H 1266	—	335H 1266	—	38 X 48	0~4	45	50
235H 1267	—	335H 1267	—	50 X 62	0~3	54	40

### B - Universal Food Grade Suction Delivery Hose

Price/Roll		Price/Meter		I.D. X O.D. (mm)	Working Pressure (Bar)		Gross Weight (Kg/Roll)	Length (m)
Number	Price ฿	Number	Price ฿		50°C	70°C		
					435H 1257	—		
435H 1258	—	535H 1258	—	32 X 41	-1~3	-1~2	34	40
435H 1259	—	535H 1259	—	38 X 48	-1~3	-1~2	43	40
435H 1260	—	535H 1260	—	50 X 62	-1~3	-1~2	66	40
435H 1261	—	535H 1261	—	63 X 80	-1~2	-1~1	56	40

## Asepsi - Flex® PVC Vacuum Hose

Asepsi-Flex is made from PVC and is smooth inside and out. The unique design resists kinking and is crushproof while remaining highly flexible for a variety of vacuum, Umbilical and conduit applications. Available in four colors.

Number	Price ฿	Mfr's	Packaging Unit Size	ID	Max. Vacuum Hg.	Standard Colors
98P1 0281	—	1E-501	25' Length	1/2"	29	Light Gray, Sterling, Sand, Surf
98P1 0282	—	1F-501	100' Length	1/2"	29	Light Gray, Sterling, Sand, Surf
98P1 0283	—	1E-625	25' Length	5/8"	29	Light Gray, Sterling, Sand, Surf
98P1 0284	—	1F-625	100' Length	5/8"	29	Light Gray, Sterling, Sand, Surf



## Corrugated Hose



**FreelinWade**

### Feature

- Working Pressure 15 PSI for Ø 1/2-1" and 10 PSI for Ø 1 1/4-1 1/2"
- Max. Vacuum 29 Hg.
- Colour Gray

### Application

An excellent vacuum and low pressure blower tubing, It's also commonly used as a conduit for bundling assortments of tubing and wiring.

Number	Price ฿	Mfr's	Packaging Unit Size	ID	Max. Vacuum Hg.	Working Pressure @25°C.	lbs./100'	No. For Cuffs
98P1 8216	—	1F-047	25' Length 250' Box 5@50'	1/2"	29	15 PSI	6.8	N/A
98P1 8217	—	1F-053	25' Length 150' Box 3@50'	5/8"	29	15 PSI	8.7	0C-058
98P1 8218	—	1F-054	50' Length	3/4"	29	15 PSI	10.0	0C-034
98P1 8219	—	1F-055	50' Length	1"	29	15 PSI	14.0	0C-100
98P1 8220	—	1F-056	50' Length	1-1/4"	29	13 PSI	20.0	0C-114
98P1 8221	—	1F-057	50' Length	1-1/2"	29	9 PSI	26.0	0CH-112
98P1 8222	—	1F-058	50' Length	1-3/4"	28	7 PSI	34.0	N/A