

Flexible Hose

Flexible Metal Hose Assemblies - 304, 316 Stainless Steel

Highly flexible hoses absorb vibration and compensate for Misalignment. Hose assemblies have a 304 Stainless steel braid. Ideal for Air compressors, Liquid and Vacuum pumps and Pump suction discharge lines. 316 Stainless steel hoses offer better.



HOSE MASTER Inc.



304, 316 Stainless Steel : MNPT X 150-LB. FNPT UNION, MNPT X MNPT, Max. Temp. 648 °C.

Dia. (In.)	L (In.)	Static Min. Bend Radius (In.)	Fitting Type A					Fitting Type B				
			Max. Working Pressure @21°C	304 Stainless Steel Male NPT X 150 lb 304 Stainless Steel Female NPT Union		316 Stainless Steel MNPT X 316 Stainless Steel 150 lb FNPT Union		Max. Working Pressure @21°C	304 Stainless Steel Male NPT X 304 Stainless Steel Male NPT		316 Stainless Steel MNPT X 316 Stainless Steel MNPT	
				Number	Price ฿	Number	Price ฿		Number	Price ฿	Number	Price ฿
1/4"	12	1.0	300	880B 6583	—	910B 6583	—	1800	369P 6583	—	269P 6583	—
1/4"	18	1.0	300	880B 6584	—	910B 6584	—	1800	369P 6584	—	269P 6584	—
1/4"	24	1.0	300	880B 6585	—	910B 6585	—	1800	369P 6585	—	269P 6585	—
1/4"	36	1.0	300	880B 6586	—	910B 6586	—	1800	369P 6586	—	269P 6586	—
3/8"	12	1.2	300	880B 6587	—	910B 6587	—	1558	369P 6587	—	269P 6587	—
3/8"	18	1.2	300	880B 6588	—	910B 6588	—	1558	369P 6588	—	269P 6588	—
3/8"	24	1.2	300	880B 6589	—	910B 6589	—	1558	369P 6589	—	269P 6589	—
3/8"	36	1.2	300	880B 6590	—	910B 6590	—	1558	369P 6590	—	269P 6590	—
1/2"	12	1.5	300	880B 6591	—	910B 6591	—	1186	369P 6591	—	269P 6591	—
1/2"	18	1.5	300	880B 6592	—	910B 6592	—	1186	369P 6592	—	269P 6592	—
1/2"	24	1.5	300	880B 6593	—	910B 6593	—	1186	369P 6593	—	269P 6593	—
1/2"	36	1.5	300	880B 6594	—	910B 6594	—	1186	369P 6594	—	269P 6594	—
3/4"	12	2.1	300	880B 6595	—	910B 6595	—	898	369P 6595	—	269P 6595	—
3/4"	18	2.1	300	880B 6596	—	910B 6596	—	898	369P 6596	—	269P 6596	—
3/4"	24	2.1	300	880B 6597	—	910B 6597	—	898	369P 6597	—	269P 6597	—
3/4"	36	2.1	300	880B 6598	—	910B 6598	—	898	369P 6598	—	269P 6598	—
1"	12	2.7	300	880B 6599	—	910B 6599	—	718	369P 6599	—	269P 6599	—
1"	18	2.7	300	880B 6600	—	910B 6600	—	718	369P 6600	—	269P 6600	—
1"	24	2.7	300	880B 6601	—	910B 6601	—	718	369P 6601	—	269P 6601	—
1"	36	2.7	300	880B 6602	—	910B 6602	—	718	369P 6602	—	269P 6602	—
1 1/4"	12	3.1	300	880B 6603	—	910B 6603	—	645	369P 6603	—	269P 6603	—
1 1/4"	18	3.1	300	880B 6604	—	910B 6604	—	645	369P 6604	—	269P 6604	—
1 1/4"	24	3.1	300	880B 6605	—	910B 6605	—	645	369P 6605	—	269P 6605	—
1 1/4"	36	3.1	300	880B 6606	—	910B 6606	—	645	369P 6606	—	269P 6606	—
1 1/2"	12	3.9	300	880B 6607	—	910B 6607	—	531	369P 6607	—	269P 6607	—
1 1/2"	18	3.9	300	880B 6608	—	910B 6608	—	531	369P 6608	—	269P 6608	—
2"	18	5.1	300	880B 6612	—	910B 6612	—	449	369P 6612	—	269P 6612	—
2"	24	5.1	300	880B 6613	—	910B 6613	—	449	369P 6613	—	269P 6613	—
2"	36	5.1	300	880B 6614	—	910B 6614	—	449	369P 6614	—	269P 6614	—

Super Flex Metal Hose Assemblies

Max. Temp. 648 °C. 321 Stainless steel hose with 304 Stainless steel braid material. Enhanced bend radius and Flexibility minimizes connection misalignment. Use wherever vibration may be a concern.



HOSE MASTER Inc.

Dia. (In.)	Static Min. Bend Radius (In.)	Max. Working Pressure @21°C	Length 12"		Length 18"		Length 24"		Length 36"	
			Number	Price ฿	Number	Price ฿	Number	Price ฿	Number	Price ฿
1/4"	0.9	300	68D1 2003	—	786H 6583	—	109P 6583	—	219P 6583	—
3/2"	1.0	300	68D1 2004	—	786H 6584	—	109P 6584	—	219P 6584	—
1/2"	1.2	300	68D1 2005	—	786H 6585	—	109P 6585	—	219P 6585	—
3/4"	1.7	300	68D1 2006	—	786H 6586	—	109P 6586	—	219P 6586	—
1"	2.1	300	68D1 2007	—	786H 6587	—	109P 6587	—	219P 6587	—
1 1/4"	2.5	300	68D1 2008	—	786H 6588	—	109P 6588	—	219P 6588	—
1 1/2"	3.1	300	68D1 2009	—	786H 6589	—	109P 6589	—	219P 6589	—