



316 Stainless Steel Ball Valves with Compression Tube Fitting or BSPP Connections



Compression Tube Fittings



Female X Female Threaded



Body, Ball and Blowout - Proof stem are type 316 stainless steel. Seat and packing are glass-filled PTFE. Lever handles are made of type 302 stainless steel with a vinyl grip and are lockable using a padlock with a shackle diameter up to 5/16", Unless noted. Connections : Double - Ferrule compression tube fittings or BSPP (British Standard Pipe Parallel) threaded fittings. Ball valves with compression tube fittings - These are ideal for instrumentation applications. Can be used with Yor-Lok, Swagelok, Parker-A-Lok, Gyrolok, Hy-Lok and Letlok tube fittings. For compression tube fittings, Ball valves with BSPP Threads -Ideal for confined areas where a BSPP connection is required.

Maximum Pressure : W.O.G. (Water, Oil, Inert Gas) : 1000 psi @ 70°C; W.S.P. (Working Steam Pressure) : Not Rated. Vacuum Rating : Not Rated, Temperature Range : -51° to 93° C. Ports : Standard.

For Tube OD	End-to-End Lg.	Compression Tube Fittings		End-to-End Lg.	Female x Female BSPP Threads		End-to-End Lg.	Male x Female BSPP Threads	
		Number	Price ₪		Number	Price ₪		Number	Price ₪
1/4"	3 35/64"	4E75 7570	—	1 31/32"	4T55 7580	—	1 31/32"	4T45 4590	—
3/8"	3 35/64"	4E75 7571	—	2 23/64"	4T55 7581	—	—	—	—
1/2"	3 3/4"	4E75 7572	—	2 61/64"	4T55 7582	—	2 61/64"	4T45 4591	—
3/4"	4 29/64"	4E75 7573	—	—	—	—	—	—	—
1"	5 3/32"	4E75 7574	—	—	—	—	—	—	—

Thermoplastic 2 & 3 - Way Full Port True Union Ball Valves



- Teflon seat
- Blow proof stem
- Female NPT connections
- All psi rated at 22° C.
- Max. Temp. PVC Housing : 60° C, CPVC Housing : 98° C, Polypropylene Housing : 98° C.

3 - Way

Pipe Size (In.)	Pressure Rating (psi.)	PVC			
		EPDM Seal		Viton Seal	
		Number	Price ₪	Number	Price ₪
1/2"	150	4G05 4541	—	4G75 8547	—
3/4"	150	4G05 4542	—	4G75 8548	—
1"	150	4G05 4543	—	4G75 8549	—
1 1/4"	150	4G05 4544	—	4G75 8550	—
2 1/2"	150	4G05 4545	—	4G75 8551	—
2"	150	4G05 4546	—	4G75 8552	—

Union connections allow you to easily remove valves from your piping system without disturbing pipe connection.

Connections : PVC and CPVC sizes 1/2" Through 2" Include a pair of female NPT Threaded adapters and a pair of socket adapters. PVC and CPVC size 2 1/2" Through 4" Include only one pair of female NPT Threaded adapters. All size of polypropylene valves include only socket adapters.

2 - Way

Pipe Size (In.)	Pressure Rating (psi)	PVC				CPVC				Polypropylene	
		EPDM Seal		Viton Seal		EPDM Seal		Viton Seal		Viton Seal	
		Number	Price ₪	Number	Price ₪	Number	Price ₪	Number	Price ₪	Number	Price ₪
1/2"	232	4H05 8541	—	4H05 8550	—	4H05 8559	—	4H05 8568	—	4H05 8577	—
3/4"	232	4H05 8542	—	4H05 8551	—	4H05 8560	—	4H05 8569	—	4H05 8578	—
1"	232	4H05 8543	—	4H05 8552	—	4H05 8561	—	4H05 8570	—	4H05 8579	—
1 1/4"	232	4H05 8544	—	4H05 8553	—	4H05 8562	—	4H05 8571	—	4H05 8580	—
1 1/2"	232	4H05 8545	—	4H05 8554	—	4H05 8563	—	4H05 8572	—	4H05 8581	—
2"	232	4H05 8546	—	4H05 8555	—	4H05 8564	—	4H05 8573	—	4H05 8582	—
2 1/2"	150	4H05 8547	—	4H05 8556	—	4H05 8565	—	4H05 8574	—	4H05 8583	—
3"	150	4H05 8548	—	4H05 8557	—	4H05 8566	—	4H05 8575	—	4H05 8584	—
4"	150	4H05 8549	—	4H05 8558	—	4H05 8567	—	4H05 8576	—	4H05 8585	—

Socket, butt fusion and flanges are available through special order.