

EDB (Bolt - On) Circuit Breakers



**1-Pole
Standard**

**2-Pole
Standard**

**3-Pole
Standard**

- ▶ UL Listed as HACR type
- ▶ 480/277VAC Used with NF panelboards.

EDB Bolt on circuit breaker, Current rating 15-125 amperes,

Number of poles 1, 2, 3 minimum wire size 14 american wire gauge, Maximum Wire Size 6, 2/0 american wire gauge,

AIR rating 18K, Used on NF panelboard.

| Amps | Max. Wire Size (AWG) | 1-Pole | | | 2-Pole | | | 3-Pole | | |
|------|----------------------|--------|--------|----------|--------|--------|----------|--------|--------|----------|
| | | Mfr's | Number | Price \$ | Mfr's | Number | Price \$ | Mfr's | Number | Price \$ |

Standard, 18kA IR

| | | | | | | | | | | |
|-----|-----|-------|-----------|---|-------|-----------|---|-------|-----------|---|
| 15 | 6 | 3TW12 | 90P1 2387 | — | 3TW22 | 91P1 2387 | — | 3TW37 | 92P1 2387 | — |
| 20 | 6 | 3TW13 | 90P1 2388 | — | 3TW23 | 91P1 2388 | — | 3TW38 | 92P1 2388 | — |
| 25 | 6 | 2JWD1 | 90P1 2389 | — | 2JWG2 | 91P1 2389 | — | 3TW39 | 92P1 2389 | — |
| 30 | 6 | 3TW15 | 90P1 2390 | — | 3TW25 | 91P1 2390 | — | 3TW40 | 92P1 2390 | — |
| 35 | 2/0 | 2JWK8 | 90P1 2391 | — | 2JWL7 | 91P1 2391 | — | 3TW41 | 92P1 2391 | — |
| 40 | 2/0 | 3TW17 | 90P1 2392 | — | 3TW27 | 91P1 2392 | — | 3TW42 | 92P1 2392 | — |
| 45 | 2/0 | 2JWL3 | 90P1 2393 | — | 2KDF5 | 91P1 2393 | — | 3TW43 | 92P1 2393 | — |
| 50 | 2/0 | 2JWE4 | 90P1 2394 | — | 3TW29 | 91P1 2394 | — | 3TW44 | 92P1 2394 | — |
| 60 | 2/0 | 3TW20 | 90P1 2395 | — | 3TW30 | 91P1 2395 | — | 3TW45 | 92P1 2395 | — |
| 70 | 2/0 | 2JWF2 | 90P1 2396 | — | 3TW31 | 91P1 2396 | — | 3TW46 | 92P1 2396 | — |
| 80 | 2/0 | — | — | — | 3TW32 | 91P1 2397 | — | 3TW47 | 92P1 2397 | — |
| 90 | 2/0 | — | — | — | 2JWJ5 | 91P1 2398 | — | 3TW48 | 92P1 2398 | — |
| 100 | 2/0 | — | — | — | 3TW34 | 91P1 2399 | — | 3TW49 | 92P1 2399 | — |
| 110 | 2/0 | — | — | — | 3TW35 | 91P1 2400 | — | 3TW50 | 92P1 2400 | — |
| 125 | 2/0 | — | — | — | 2JWK4 | 91P1 2401 | — | 3TW51 | 92P1 2401 | — |

EPD (Equipment Protection Device), 30mA Trip, 18kA IR

| | | | | | | | | | | |
|----|-----|-------|-----------|---|---|---|---|---|---|---|
| 15 | 6 | 2JWC2 | 90P1 2397 | — | — | — | — | — | — | — |
| 20 | 6 | 2JWC6 | 90P1 2398 | — | — | — | — | — | — | — |
| 30 | 6 | 2JWD5 | 90P1 2399 | — | — | — | — | — | — | — |
| 40 | 2/0 | 2JWD9 | 90P1 2400 | — | — | — | — | — | — | — |
| 50 | 2/0 | 2JWE6 | 90P1 2401 | — | — | — | — | — | — | — |

Shunt Trip, Type 1021 (120VAC Control), Normally Open, 18kA IR

| | | | | | | | | | | |
|-----|-----|-------|-----------|---|-------|-----------|---|-------|-----------|---|
| 15 | 6 | 2JWC4 | 90P1 2402 | — | 2JWF8 | 91P1 2402 | — | 2JWN7 | 92P1 2402 | — |
| 20 | 6 | 2JWC8 | 90P1 2403 | — | 2JWN2 | 91P1 2403 | — | 2JWP3 | 92P1 2403 | — |
| 25 | 6 | 2JWD3 | 90P1 2404 | — | — | — | — | 2JWP7 | 92P1 2404 | — |
| 30 | 6 | 2JWD7 | 90P1 2405 | — | 2JWG5 | 91P1 2405 | — | 2JWR3 | 92P1 2405 | — |
| 40 | 2/0 | 2JWE2 | 90P1 2406 | — | 2JWG8 | 91P1 2406 | — | 2JWR8 | 92P1 2406 | — |
| 50 | 2/0 | 2JWE8 | 90P1 2407 | — | 2JWH2 | 91P1 2407 | — | 2JWT3 | 92P1 2407 | — |
| 60 | 2/0 | — | — | — | — | — | — | 2JWT9 | 92P1 2408 | — |
| 70 | 2/0 | 2JWF5 | 90P1 2408 | — | 2JWH6 | 91P1 2409 | — | 2JWU6 | 92P1 2409 | — |
| 80 | 2/0 | — | — | — | 2JWJ1 | 91P1 2410 | — | 2JWX3 | 92P1 2410 | — |
| 90 | 2/0 | — | — | — | 2JWJ9 | 91P1 2411 | — | 2JWX9 | 92P1 2411 | — |
| 100 | 2/0 | — | — | — | — | — | — | 2JWY5 | 92P1 2412 | — |