



Power Relays




G6B Subminiature Power PCB Relays



Dimension : mm



Terminal Arrangement



Specifications

- ▶ Contact rating : Standard type - 5A @ 250VAC; High-capacity type - 8A @ 250VAC.
- ▶ Power consumption : SPST-NO - 200mW 2-pole - 300mW.
- ▶ Contact material : Ag Alloy.

Fig.	Number	Price ฿	Mfr's	Contact Form	Rated Coil Voltage	Rated Coil Current
------	--------	------------	-------	--------------	--------------------	--------------------

Standard Type with Sealed Construction, Non-Latching

A1	6A53 0611	---	G6B-1114P-US-DC5	SPST-NO	5 VDC	40 mA
A1	6A53 0612	---	G6B-1114P-US-DC12	SPST-NO	12 VDC	16.7 mA
A1	6A53 0613	---	G6B-1114P-1-US-DC12	SPST-NO	12 VDC	16.7 mA
A1	6A53 0614	---	G6B-1114P-US-DC24	SPST-NO	24 VDC	8.3 mA
A1	6A53 0615	---	G6B-1114P-FD-US-DC24	SPST-NO	24 VDC	8.3 mA
A1	6A53 0616	---	G6B-1174P-FD-US-DC24	SPST-NO	24 VDC	8.3 mA
A2	6A53 0617	---	G6B-2114P-US-DC5	SPST-NO+SPST-NC	5 VDC	60 mA
A2	6A53 0618	---	G6B-2114P-US-DC6	SPST-NO+SPST-NC	6 VDC	33.3 mA
A2	6A53 0619	---	G6B-2114P-US-DC12	SPST-NO+SPST-NC	12 VDC	25 mA
A2	6A53 0620	---	G6B-2114P-1-US-DC12	SPST-NO+SPST-NC	12 VDC	16.7 mA
A2	6A53 0621	---	G6B-2114P-US-DC24	SPST-NO+SPST-NC	24 VDC	12.5 mA
A3	6A53 0622	---	G6B-2214P-US-DC5	DPST-NO	5 VDC	60 mA
A3	6A53 0623	---	G6B-2214P-US-DC12	DPST-NO	12 VDC	25 mA
A3	6A53 0624	---	G6B-2214P-US-DC24	DPST-NO	24 VDC	12.5 mA

Dual Coil Catching

A1	6A53 0625	---	G6BK-1114P-US-DC5	SPST-NO	5 VDC	40 mA
----	-----------	-----	-------------------	---------	-------	-------


High Capacity Type with Sealed Construction, Non-Latching

A1	6A53 0625	---	G6B-1174P-US-DC5	SPST-NO	5 VDC	40 mA
A1	6A53 0626	---	G6B-1174P-US-DC12	SPST-NO	12 VDC	16.7 mA
A1	6A53 0627	---	G6B-1174P-US-DC24	SPST-NO	24 VDC	8.3 mA


G6C Subminiature Power PCB Relays

Specifications

- ▶ Contact rating : SPST-NO - 10A @ 250 VAC; SPST-NO+SPST-NC - 8A @ 250VAC.
- ▶ Power consumption : 200mW.
- ▶ Contact material : Ag Alloy.



Dimension : mm



Terminal Arrangement

Fig. 1




Fig. 2




Fig.	Number	Price ฿	Mfr's	Contact Form	Rated Coil Voltage	Rated Coil Current
------	--------	------------	-------	--------------	--------------------	--------------------

Sealed, Non-Latching

A2	6H53 6028	---	G6C-1114P-US-DC5	SPST-NO	5 VDC	40mA
A2	6H53 6029	---	G6C-1114P-US-DC12	SPST-NO	12 VDC	16.7mA
A2	6H53 6030	---	G6C-1114P-US-DC24	SPST-NO	24 VDC	8.3mA
A2	6H53 6031	---	G6C-2114P-US-DC3	SPST-NO + SPST-NC	3 VDC	66.7mA
A2	6H53 6032	---	G6C-2114P-US-DC5	SPST-NO + SPST-NC	5 VDC	40mA
A2	6H53 6033	---	G6C-2114P-US-DC12	SPST-NO + SPST-NC	12 VDC	16.7mA
A2	6H53 6034	---	G6C-2114P-US-DC24	SPST-NO + SPST-NC	24 VDC	8.3mA

Semi-Sealed, Non-Latching

A1	6H53 6035	---	G6C-2117P-US-DC5	SPST-NO + SPST-NC	5 VDC	40mA
A1	6H53 6036	---	G6C-2117P-US-DC12	SPST-NO + SPST-NC	12 VDC	16.7mA

Sealed, Dual-Winding Latching Contact

A1	6H53 6037	---	G6CK-2114P-US-DC5	SPST-NO + SPST-NC	5 VDC	56mA
----	-----------	-----	-------------------	-------------------	-------	------

(Continued on following page)