

Circular Connectors

MS/Standard Cylindrical MIL - C - 5015 Type Connectors



(Continued from previous page)


MS3102A Sreies Wall Mount Receptacles

Number	Price ₪	Mfr's	Contacts	Insert Arrangem.	Dimensions	
					A	B
1T05 5415	---	MS3102A10SL-4P	2	10SL-4	0.625"	0.719"
1T05 5416	---	MS3102A10SL-3P	3	10SL-3	0.625"	0.719"
1T05 5417	---	MS3102A14S-2S	4	14S-2	0.750"	0.906"
1T05 5418	---	MS3102A14S-5P	5	14S-5	0.750"	0.906"
1T05 5419	---	MS3102A14S-5S	5	14S-5	0.750"	0.906"
1T05 5420	---	MS3102A14S-6P	6	14S-6	0.750"	0.906"
1T05 5421	---	MS3102A14S-6S	6	14S-6	0.750"	0.906"
1T05 5422	---	MS3102A16S-1P	7	16S-1	0.875"	0.969"
1T05 5423	---	MS3102A16S-1S	7	16S-1	0.875"	0.969"
1T05 5424	---	MS3102A18-10P	4	18-10	1.000"	1.062"
1T05 5425	---	MS3102A18-11P	5	18-11	1.000"	1.062"
1T05 5426	---	MS3102A18-1P	10	18-1	1.000"	1.062"
1T05 5427	---	MS3102A18-1S	10	18-1	1.000"	1.062"
1T05 5428	---	MS3102A18-8P	8	18-8	1.000"	1.062"
1T05 5429	---	MS3102A20-27P	14	20-27	1.125"	1.156"
1T05 5430	---	MS3102A20-29S	17	20-29	1.125"	1.156"
1T05 5431	---	MS3102A22-20S	9	22-20	1.250"	1.250"

MS3102E Sreies Wall Mount Receptacles

Number	Price ₪	Mfr's	Contacts	Insert Arrangem.	Dimensions	
					A	B
3J31 3840	---	MS3102E10SL-3P	3	10SL-3	0.625"	1.000"
3J31 3841	---	MS3102E10SL-3S	3	10SL-3	0.625"	1.000"
3J31 3842	---	MS3102E10SL-4P	2	10SL-4	0.625"	1.000"
3J31 3843	---	MS3102E14S-2P	4	14S-2	0.750"	1.188"
3J31 3844	---	MS3102E14S-2S	4	14S-2	0.750"	1.188"
3J31 3845	---	MS3102E14S-5P	5	14S-5	0.750"	1.188"
3J31 3846	---	MS3102E14S-6P	6	14S-6	0.750"	1.188"
3J31 3847	---	MS3102E14S-6S	6	14S-6	0.750"	1.188"
3J31 3848	---	MS3102E-14S-7S	3	14S-7	0.750"	1.188"
3J31 3849	---	MS3102E16S-1P	7	16S-1	0.875"	1.281"
3J31 3850	---	MS3102E-16S-1S	7	16S-1	0.875"	1.281"
3J31 3851	---	MS3102E-16-10P	3	16-10	0.875"	1.281"
3J31 3852	---	MS3102E-18-1S	10	18-1	1.000"	1.375"
3J31 3853	---	MS3102E18-1P	10	18-7	1.000"	1.375"
3J31 3854	---	MS3102E18-11P	5	18-11	1.000"	1.375"
3J31 3855	---	MS3102E18-12P	6	18-12	1.000"	1.375"
3J31 3856	---	MS3102E20-29P	17	20-29	1.125"	1.500"
3J31 3857	---	MS3102E20-29S	17	20-29	1.125"	1.500"
3J31 3858	---	MS3102E22-14P	19	22-14	1.250"	1.625"
3J31 3859	---	MS3102E22-22P	4	22-22	1.250"	1.625"

MS/Standard Sealing Gaskets



Plain flat gasket. Waterproof and pressure sealing features. Flange Mount.

Material : Synthetic rubber.



Number	Price ₪	Mfr's	Shell size
9B20 7571	---	10-40450-10	10, 10S, 10SL
9B20 7572	---	10-40450-12	12, 12S, 12SL
9B20 7573	---	10-40450-14	14, 14S
9B20 7574	---	10-40450-16	16, 16S
9B20 7575	---	10-40450-22	22

MS3102R Sreies Wall Mount Receptacles

Number	Price ₪	Mfr's	Contacts	Insert Arrangem.	Dimensions	
					A	B
8C50 4043	---	MS3102R10SL-3P	3	10SL-3	0.625"	0.719"
8C50 4044	---	MS3102R10SL-4P	2	10SL-4	0.625"	0.719"
8C50 4045	---	MS3102R14S-2P	4	14S-2	0.750"	0.906"
8C50 4046	---	MS3102R14S-2S	4	14S-2	0.750"	0.906"
8C50 4047	---	MS3102R14S-5P	5	14S-5	0.750"	0.906"
8C50 4048	---	MS3102R14S-5S	5	14S-5	0.750"	0.906"
8C50 4049	---	MS3102R14S-6P	6	14S-6	0.750"	0.906"
8C50 4050	---	MS3102R14S-6S	6	14S-6	0.750"	0.906"
8C50 4051	---	MS3102R14S-7P	3	14S-7	0.750"	0.906"
8C50 4052	---	MS3102R14S-7S	3	14S-7	0.750"	0.906"
8C50 4053	---	MS3102R16-10P	3	16-10	0.875"	0.969"
8C50 4054	---	MS3102R16-10S	3	16-10	0.875"	0.969"
8C50 4055	---	MS3102R16S-1P	7	16S-1	0.875"	0.969"
8C50 4056	---	MS3102R16S-1S	7	16S-1	0.875"	0.969"
8C50 4057	---	MS3102R16-11P	2	16-11	0.875"	0.969"
8C50 4058	---	MS3102R-18-1P	10	18-1	1.000"	1.062"
8C50 4059	---	MS3102R18-1S	10	18-1	1.000"	1.062"
8C50 4060	---	MS3102R18-11P	5	18-11	1.000"	1.062"
8C50 4061	---	MS3102R20-27P	14	20-27	1.125"	1.156"
8C50 4062	---	MS3102R20-27S	14	20-27	1.125"	1.156"

PRE - Earth/Fmlb Connectors



DL Series Pre - Earth/First Mate Last Break (FMLB)

Connectors are designed for applications where a protective circuit from the ground contact to the shell is a safety requirement. Offered in straight plug and box mount receptacle styles. Main joint gasket between plug and receptacle shells provides superior moisture sealing.

Certified to european safety standards for use in factory automation, machine tool and process control applications. Meet MIL-C-5015 Dimensions and performance where applicable.

Pre-Earth (Grounded contact) Design
First mate, Last break capability
Class IP67 protection in mated condition
Conform to european safety standards
Standard black zinc plating, CE compliant

Number	Price ₪	Mfr's	No. of Contacts	Amps
3C20 1467	---	DL3106A10SL-3S	3	13
3C20 1468	---	DL3106A18-10S	4	23
3C20 1469	---	DL3106A18-12S	6	13
3C20 1470	---	DL3106A20-15S	7	23