

Lithium Batteries

Hi - Temp Coin Cell Lithium Batteries

Fig.	Number	Price ฿	Mfr's	Capacity (mAh)	Dimensions (mm)
A	1225 E091	---	BR1225A/FAN	48	12.5 X 2.5
A	1226 E092	---	BR1225A/HAN	48	12.5 X 2.5
A	1227 E093	---	BR1225A/HBN	48	12.5 X 2.5
B	1228 E094	---	BR1632A/FAN	120	16.0 X 3.2
B	1229 E095	---	BR1632A/GAN	120	16.0 X 3.2
B	1230 E096	---	BR1632A/HAN	120	16.0 X 3.2
B	1231 E097	---	BR1632A/VAN	120	16.0 X 3.2
C	1232 E098	---	BR2330A/FAN	255	23.0 X 3.0
C	1233 E099	---	BR2330A/GAN	255	23.0 X 3.0
D	1236 E102	---	BR2477A/FBN	1000	24.5 X 7.7
D	1237 E103	---	BR2477A/GAN	1000	24.5 X 7.7
D	1238 E104	---	BR2477A/HBN	1000	24.5 X 7.7
E	1240 E106	---	CR2412	100	23.0 X 5.4
E	1241 E107	---	CR2450	100	24.0 X 5.0



Lithium Coin Cells - 3V

BR Series

- Lithium Poly - Carbonmonofluoride.
- Stable voltage discharge.
- Suitable for low drain devices.
- Suitable for high temperature applications
- Operating temperature range : -30° ~ +80°C.



CR Series

- Lithium manganese dioxide.
- Tapered voltage discharge.
- Suitable for high drain devices.
- Operating temperature range : -30° ~ +60°C.

Panasonic

Number	Price ฿	Mfr's	Capacity (mAh)	Dimensions (mm)
03P5 1091	---	BR1216	25	12.5 X 1.6
03P5 1092	---	BR1225	48	12.5 X 2.0
03P5 1093	---	BR1616	48	16.0 X 2.5
03P5 1094	---	BR2032	190	20.0 X 3.2
03P5 1095	---	BR2325	165	23.0 X 2.5
03P5 1096	---	BR2330	255	23.0 X 3.0
03P5 1097	---	BR3032	500	30.0 X 3.2
03P5 1098	---	CR1025	30	10.0 X 2.5
03P5 1099	---	CR1216	25	12.0 X 1.6
03P5 1100	---	CR1220	35	12.0 X 2.0
03P5 1101	---	CR1616	55	16.0 X 1.6
03P5 1102	---	CR1620	75	16.0 X 2.0
03P5 1103	---	CR1632	125	16.0 X 3.2
03P5 1104	---	CR2012	55	20.0 X 1.2
03P5 1105	---	CR2016	90	20.0 X 1.6
03P5 1106	---	CR2025	165	20.0 X 2.5

Lithium Pin Type - 3V

Panasonic



BR Series

- Suitable for low drain devices.
- Suitable for high temperature applications
- Operating temperature range : -30° ~ +80°C.

Number	Price ฿	Mfr's	Capacity (mAh)	Dimensions (mm)
425B 6011	---	BR425	25	4.2 X 25.9
425B 6012	---	BR435	30	4.2 X 35.9

Lithium Cylindrical Cells - 3V

- High energy density.
- Long shelf life. Operating temp. range : -40° ~ +85°C.
- High rate discharge.



Fig.	Number	Price ฿	Mfr's	Capacity (mAh)	Dimensions (mm)
A	58P5 1200	---	BR-2/3ASSP	1200	17.0 X 33.5
B	58P5 1201	---	BR-2/3AT2SP	1200	17.0 X 33.5
C	58P5 1202	---	BR-2/3AE2SP	1200	17.0 X 33.5
A	58P5 1203	---	BR-A	1800	17.0 X 45.5
A	58P5 1204	---	BR-C	5000	26.0 X 50.0
B	58P5 1205	---	BR-CT2SP	5000	26.0 X 50.0